

Guide for Drill

Field of Invention

The present invention relates to drills and, more particularly, to a guide for drills while boring a door with holes for receiving a lock.

Background of Invention

Referring to Figure 8, there is shown a conventional guide 60 for drills (not shown) while boring a door with holes for a lock (not shown). The conventional guide 60 includes a first portion 62 and a second portion 64 extending perpendicular to the first portion 62. A hole 66 is defined in the first portion 62. On the first portion 62 extends a rim 68 around the hole 66. A hole 70 is defined in the second portion 64. On the second portion 64 extends a rim 72 around the hole 70. Two holes 74 are defined in the second portion 64. Referring to Figure 9, a door D1 is shown. The door D1 includes a front face, a rear face and a side between the front and rear faces. The first portion 62 is put against the front face of the door D1. The second portion 64 is put against the side of the door D1. Two screws 76 are driven into the side of the door D1 through the holes 74 in order to secure the guide 60 to the door D1. A first drill (not shown) can be put into the hole 66 and guided by means of the rim 68. The first drill can be driven through the door D1 from the front face to the rear face in order to bore a first hole (not shown) in the door D1. A second drill (not shown) can be put into the hole 70 and guided by means of the rim 72. The second drill can be driven into the door D1 from the side in order to bore a second hole (not shown) in the

1 door D1. The first hole is communicated with the second hole. A lock
2 (not shown) can be put in the first hole, and a tongue of the lock can be
3 put in the second hole. There is a need to bore the first hole in a
4 different position. This need cannot be satisfied due to the first portion
5 62 made of a fixed size. Furthermore, it is required that the second hole
6 be located in the middle of the side of the door D1. This requirement
7 cannot be fulfilled if the guide 60 is used for another door D2 of a
8 different thickness shown in Figure 10 due to the second portion 64 made
9 of a fixed size. Moreover, after removal of the guide 60 from the door
10 D1 or D2, two holes are left in the side because of the screws 74, and this
11 is not desired.

12
13 The present invention is therefore intended to obviate or at least alleviate
14 the problems encountered in prior art.

15 16 **Summary of Invention**

17 It is an objective of the present invention to provide drills with a guide
18 making it possible to bore a door with a hole at various distances from a
19 side of the door.

20
21 It is another objective of the present invention to provide drills with a
22 guide ensuring that a hole be bored in the middle of a side of a door
23 regardless of the thickness of the door.

24
25 According to the present invention, a guide is provided for guiding a first
26 drill and a second drill while boring a door with holes for receiving a lock.

1 The guide includes a first element, a second element, a third element, a
2 first threaded bolt and a second threaded bolt. The first element guides
3 the first drill and abuts a first face of the door. The second element
4 guides the first drill and abuts a second face of the door. The third
5 element abuts a side of the door. The first threaded bolt is connected
6 between the first element and the third element so that the first element is
7 movable on the first face of the door. The first threaded bolt is operable
8 for driving the first element against the first face of the door. The
9 second threaded bolt is connected between the second element and the
10 third element so that the second element is movable on the second face of
11 the door. The second threaded bolt is operable for driving the second
12 element against the second face of the door.

13
14 Other objects, advantages and novel features of the invention will become
15 more apparent from the following detailed description in conjunction
16 with the attached drawings.

17 18 **Brief Description of Drawings**

19 The present invention will be described through detailed illustration of
20 two embodiments referring to the drawings.

21
22 Figure 1 is a perspective view of a guide for drills according to a first
23 embodiment of the present invention.

24
25 Figure 2 is an exploded view of the guide of Figure 1.

1 Figure 3 is a cross-sectional view of the guide of Figure 1 used for a door.

2

3 Figure 4 is similar to Figure 3 but shows the guide in a different position
4 for boring the door with a hole at another distance from a side of the door.

5

6 Figure 5 is similar to Figure 3 but shows the guide in a different position
7 for boring the door with a hole in a position biased from the middle of a
8 side of the door.

9

10 Figure 6 is similar to Figure 3 but shows the guide used for a thicker door.

11

12 Figure 7 is an exploded view of a guide for drills according to a second
13 embodiment of the present invention.

14

15 Figure 8 is a perspective view of a conventional guide for drills.

16

17 Figure 9 is a cross-sectional view of the conventional guide of Figure 8
18 used for a door.

19

20 Figure 10 is similar to Figure 9 but shows the conventional guide used for
21 a thicker door.

22

23 **Detailed Description of Embodiments**

24 Referring to Figure 1, according to a first embodiment of the present
25 invention, a guide is provided for drills (not shown) while boring a door
26 with holes for receiving a lock. The guide includes a first element 10, a

1 second element 20 and a third element 30.

2
3 Referring to Figure 2, the first element 10 includes a rim 11 formed on a
4 first portion thereof and a bracket 12 raised from a second portion thereof.
5 In the first portion of the first element 10 is defined a window 14 around
6 which the rim 11 extends. Two holes 16 and 18 are defined in the
7 bracket 12.

8
9 The second element 20 includes a rim 21 formed on a first portion thereof
10 and a bracket 22 raised from a second portion thereof. In the first
11 portion of the second element 20 is defined a window 24 around which
12 the rim 21 extends. Two holes 26 and 28 are defined in the bracket 22.

13
14 The third element 30 includes a first portion 31, a second portion 32 and a
15 third portion 33 formed between the first portion 31 and the second
16 portion 32. A threaded hole 34 is defined in the first portion 31 of the
17 third element 30. A threaded hole 35 is defined in the second portion 32
18 of the third element 30. A rim 36 is formed on the third portion 33 of
19 the third element 30. In the third portion 33 of the third element 30 is
20 defined a window 38 around which the rim 36 extends.

21
22 Referring to Figure 3, a door 50 is shown. The door 50 includes a first
23 face 51, a second face 52 and a side 53 between the first face 51 and the
24 second face 52.

25
26 The first element 10 is put against the first face 51 of the door 50. The

1 second element 20 is put against the second face 52 of the door 50. The
2 third portion 33 of the third element 30 is put against the side 53 of the
3 door 50. The first portion 31 of the third element 30 is covered via the
4 bracket 12. The second portion 32 of the third element 30 is covered via
5 the bracket 22. A first threaded bolt 41 is driven into the threaded hole
6 34 through the hole 16. A second threaded bolt 42 is driven into the
7 threaded hole 35 through the hole 26. Thus, the guide is secured to the
8 door 50.

9

10 In order to bore a first hole (not shown) in the door 50, a first drill (not
11 shown) is put into the window 14 or 24, guided via the rim 11 or 21.
12 The first drill is driven from the first face 51 to the second face 52 or
13 from the second face 52 to the first face 51. In order to bore a second
14 hole (not shown) in the door 50, a second drill (not shown) is put into the
15 window 38, guided via the rim 36. The second drill is driven into the
16 door 50 from the side 53. The first hole is communicated with the
17 second hole. A lock (not shown) can be put in the first hole, and a
18 tongue of the lock can be put in the second hole.

19

20 Figure 4 is similar to Figure 3 but shows that the first threaded bolt 41 is
21 driven into the threaded hole 34 through the hole 16 and that the second
22 threaded bolt 42 is driven into the threaded hole 35 through the hole 26.
23 Thus, the second hole can be bored in the door 50 at another distance
24 from the side 53.

25

26 Figure 5 is similar to Figure 3 but shows the guide in a different position

1 where the center of the window 38 is not aligned with the middle of the
2 side 53 of the door 50. Accordingly, the center of the second hole is
3 biased from the middle of the side 53 of the door 50.

4.

5 Figure 6 is similar to Figure 3 but shows the guide used for a thicker door
6 55. Thus, the second hole is still aligned with the middle of a side of the
7 door 55.

8

9 Figure 7 shows a guide according to a second embodiment of the present
10 invention. The second embodiment is identical to the first embodiment
11 except for substituting a slot 19 for the holes 16 and 18 and substituting a
12 slot 29 for the holes 26 and 28.

13

14 The present invention has been described via detailed illustration of two
15 embodiments. Those skilled in the art can derive variations from the
16 embodiments without departing from the scope of the present invention.
17 Therefore, the embodiments shall not limit the scope of the present
18 invention defined in the claims.

19

20